

Selection Bias

Nate Wells

Math 243: Stat Learning

October 6th, 2021

Outline

In today's class, we will...

- Discuss data from homework 3 (Ames House Prices)

Section 1

Ames House Price Data

Overview

- Students fit models of varying complexity based on data on 66 predictors for 1808 houses.

Overview

- Students fit models of varying complexity based on data on 66 predictors for 1808 houses.
- Models were assessed by computing rMSE on a test set of 597 houses.
- Additionally, to assess variability, rMSE was computed on 20 bootstrap samples from the test data.

Overview

- Students fit models of varying complexity based on data on 66 predictors for 1808 houses.
- Models were assessed by computing rMSE on a test set of 597 houses.
- Additionally, to assess variability, rMSE was computed on 20 bootstrap samples from the test data.
- The median model rMSE was \$33,249.21.
- The median model standard deviation in rMSE on bootstrap samples was \$1,890 \$.


Overview

- Students fit models of varying complexity based on data on 66 predictors for 1808 houses.
- Models were assessed by computing rMSE on a test set of 597 houses.
- Additionally, to assess variability, rMSE was computed on 20 bootstrap samples from the test data.
- The median model rMSE was \$33,249.21.
- The median model standard deviation in rMSE on bootstrap samples was \$1,890 \$.
- The lowest three model rMSE were

Name	Taylor	Maxwell	Robin
rMSE	\$23,405	\$23,507	\$24,084
SD	\$1,415	\$1,202	\$1,123

Results


Model rMSE, Based on 20 Bootstraps from Test Data



Red dot indicates mean rMSE

Results

Model rMSE, Based on 20 Bootstraps from Test Data



Retrospective

Trends:

Retrospective

Trends:

- Models with more predictors tended to do better than models with fewer predictors

Retrospective

Trends:

- Models with more predictors tended to do better than models with fewer predictors
- Models with 0 interaction terms tended to do better than those with 1 interaction

Retrospective

Trends:

- Models with more predictors tended to do better than models with fewer predictors
- Models with 0 interaction terms tended to do better than those with 1 interaction
- Models that transformed key predictors tended to do better than those that did not

Retrospective

Trends:

- Models with more predictors tended to do better than models with fewer predictors
- Models with 0 interaction terms tended to do better than those with 1 interaction
- Models that transformed key predictors tended to do better than those that did not
- Performing log or root transformation moderately reduced test MSE

Retrospective

Trends:

- Models with more predictors tended to do better than models with fewer predictors
- Models with 0 interaction terms tended to do better than those with 1 interaction
- Models that transformed key predictors tended to do better than those that did not
- Performing log or root transformation moderately reduced test MSE
- The full model was near the front of the pack, while the simple model using just 1 predictor (`Gr_Liv_Area`) was at the back.

Retrospective

Trends:

- Models with more predictors tended to do better than models with fewer predictors
- Models with 0 interaction terms tended to do better than those with 1 interaction
- Models that transformed key predictors tended to do better than those that did not
- Performing log or root transformation moderately reduced test MSE
- The full model was near the front of the pack, while the simple model using just 1 predictor (`Gr_Liv_Area`) was at the back.

Further Investigation (Homework 5):

- Use `regsubsets` to assist with feature selection
- Use a cross-validation to assess and compare model performance